

CREATIVE EFFECT PRODUCT GROUP

NIPPON PAINT CRACKLE (CRACKING FLUID)

PRODUCT DESCRIPTION

A water-based special resin-containing decorative middle coat cracking material which cracks the paint to be applied over it for an antique look.

APPLICATION SURFACES

Surface needs to be pasted to apply Nippon Paint Crackle. Old painted, glass textile and wallpaper surfaces should be pasted with Nippon Paint Interior Paste.

APPLICATION: Ensure the surface to apply Nippon Paint Crackle is even, stable, dry, clean, and in a well condition to hold the paint. Paste the surface absolutely with Nippon Paint Interior Paste. Sand the pasted surface apply Nippon Paint Interior Paste Primer and complete the surface preparation.

After Nippon Paint Interior Paste dries, apply colored Nippon Paint Leona with a thin pile roller. After the paint dries, cover the edges of the application surface with a 0.5 cm masking tape. Apply Nippon Paint Crackle on it with a thin pile roller and remove the masking tapes.

4 hours after the application of Nippon Paint Crackle, apply any chosen color of Nippon Paint Leona with a thin pile roller. Avoid too much combing and do not tamper the surfaces which start cracking. Any combing after the cracking begins would damage the pattern.

• Apply between +10°C and +35°C.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

TECHNICAL SPECIFICATIONS:

Color: Transparent

Density: 1.00 ± 0.05 g/ml

THINNING

Ready to use.

DRYING TIME (at 20°C, 65% RH)

Touch Dry: 30 minutes

Second Coat Application: 4 hours

Full dry: 24 hours

GLOSS: Silky Matte.

CONSUMPTION

Ranges between 7-10 m² per liter for single coat depending on surface absorbency.

Perform a controlled sample run to estimate the precise consumption.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE:

2.5 L, 1.25 L



This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Üral Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - www.nipponboya.com

