



WOOD PROTECTION PRODUCTS

NIPPON PAINT AQUA WOOD PRIMER

PRODUCT DESCRIPTION

A primer that can be thinned with water and used under stain blocking paint.

SPECIFICATIONS

Thin with water. Environmentally-friendly and odorless. High adherence, easy-to-sand, fast-dry.

APPLICATION SURFACES

Ensures high-adherence when applied as a primer on old painted interior or exterior surfaces (dispersion, synthetic). Improves the coverage and resistance of top coat applications on wood, zinc, hard PVC and many other critical surfaces. Perform a controlled sample run before applying on high-risk surfaces.

APPLICATION

The application surface should be clean, cleared of oil and other non-load bearing residues. Wipe the surface with a cloth dampened with cellulose thinner if the surface contains resin. Sand metal, hard PVC etc. glossy surfaces before application. Can be applied with either a brush, roller or spray gun. It should be impregnated with transparent Nippon Paint Gel Wood Colorant or transparent Nippon Paint Wood Impregnation before priming on raw wooden surfaces or on old surfaces with completely removed paint. After Nippon Paint Aqua Wood Primer is applied, the surface should be sanded with no. 280 sandpaper before beginning to paint.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

THINNING

Use fresh water to thin by 5%, if required.

Mix before applying.

DRYING TIME (at 20°C, 65% RH)

Second Coat Application: 6- 8 hours (drying time can increase at higher relative humidity and lower temperature values).

CONSUMPTION

Can be applied on an area of 8-10 m² in a single coat with 1 Liter based on the type and absorbency of the wood. Color and consumption may vary depending on the wood type, surface state, number of coats and application method. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

15 L, 2.5 L, 0.75 L

Pose No.

Y.25.001/03

Rate No.

04,555/04

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

BETEK BOYA VE KIMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - www.nipponboya.com





This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Ural Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - www.nipponboya.com

